

SUPERVENTOR 124T



Built Better To Last Longer



TWO MODELS IN ONE FOR SMALL OR MEDIUM SIZED HOMES!

- 1 Industry first field selectable CFM capacity options;
Option 1) homes up to 1750 sq ft.
Option 2) homes up to 3000 sq ft.
- 2 Space saving top port design.
- 3 Built-in central remote control (Scout) with intermittent fan function.
- 4 Built in dehumidistat: Automatically controls excess humidity.
- 5 Built-in furnace fan interlock.
- 6 Optional remote controls available in a variety of color options (white, ivory or almond.)
- 7 High efficiency Coroplast core (up to 91%); easy maintenance, lifetime warranty.
- 8 Energy efficient centrifugal motors ensure long life and low cost operation.
- 9 State-of-the-art recirculatory damper defrost system, eliminates the possibility of core freeze up and negative pressure.
- 10 Aluminum framed, permanent washable filters.
- 11 Illuminated ON/OFF switch.
- 12 Integral Balancing Dampers.
- 13 Optional (EVR) core available for optimal cooling season effectiveness.



Specifications		
Description	SHRV 100T	SHRV 124T
Length	27 5/8	27 5/8
Width	21 3/8	21 3/8
Height	18 3/4	18 3/4
VAC @ 60 Hz	120	120
Amps	2	2
Shipping Weight Lbs	80	80
Airflow	C.F.M. Against External Static Pressure (each air stream)	
.7"	64	84
.6"	68	98
.5" (125 Pa)	72	110
.4" (100 Pa)	78	122
.3" (75 Pa)	83	135
.2" (50 Pa)	87	146
.1" (25 Pa)	92	155
Built in Dehumidistat	Yes	Yes
Sensible Effectiveness	87%	91%

Lifetime Warranty:

Limited Lifetime Warranty on heat exchange core and full five year warranty on electrical components.
All models CSA approved.

Distributed By:



PRINTED IN CANADA

Canada Patent Registration 052580451
U.S. Pat Pend
Application# 10-712681



Summerraire Mfg.
Peterborough, ON. Canada K9J 7B1
(705)745-4736